

Engineered for long-term regulatory compliance

Novec fluids are not targeted for regulatory phasedown, unlike conventional solvents such as hydrochlorofluorocarbons (such as HCFC-225) and hydrofluorocarbons (HFCs like Vertrel™ XF specialty fluid from Chemours). Novec fluids are also a safer alternative to n-propyl bromide (nPB) and trichloroethylene (TCE) because of their wide margin of safety.



Let's get started—together

Not sure which Novec fluid is right for your particular application? We are here to help! Please use the contact information below to learn more and get started today. Or visit [3M.com/Novec](https://www.3m.com/Novec) for product specific information.

The 3M™ Novec™ Brand Family

The Novec brand is the hallmark for a variety of proprietary 3M products. Although each has its own unique formula and performance properties, all Novec products are designed in common to address the need for safe, effective, sustainable solutions in industry-specific applications. These include precision and electronics cleaning, heat transfer, fire protection, protective coatings, immersion cooling, advanced insulation media replacement solutions and several specialty chemical applications.

3M™ Novec™ Engineered Fluids • 3M™ Novec™ Aerosol Cleaners • 3M™ Novec™ 1230 Fire Protection Fluid • 3M™ Novec™ Electronic Grade Coatings • 3M™ Novec™ Electronic Surfactants • 3M™ Novec™ Dielectric Fluids

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Materials Solutions Division

3M Center, Building 224-3N-11
St. Paul, MN 55144-1000 USA

Phone 1-800-810-8513
Web www.3m.com

Please recycle. Printed in USA.
©3M 2017. All rights reserved.
Issued: 2/17 11966HB
60-5002-0983-2

3M and Novec are Trademarks of 3M.
Used under license by 3M subsidiaries and affiliates.
Vertrel is a trademark of The Chemours Company.



3M

Novec[™]

Brand



**3M[™] Novec[™]
Engineered Fluids**

for coating, cleaning
and lubricant formulations

All the performance. No compromise.

3M Science. Applied to Life.[™]

3M™ Novec™ Engineered Fluids for coating, cleaning and lubricant formulations

No trade-offs. Just results.

To formulate quality products, you need solvents that set a new standard of performance.

When creating new coatings, cleaners and lubricants, you're always looking for new ways to push performance higher so your customers see better results. This is where your choice of solvent makes a big difference—the performance and quality of the fluid you choose can significantly impact the quality of your final product.

At 3M, we understand it can sometimes be a challenge to find a balanced solution for your formulations. You may think you have to sacrifice safety, sustainability or both for high performance. But with 3M™ Novec™ Engineered Fluids, a proprietary family of safe and sustainable solvents, there is no compromise.

Novec fluids offer an outstanding combination of performance, safety and environmental properties, allowing you to provide your customers with unique new solutions that get the job done. And with their excellent materials compatibility, you'll have the formulating freedom you need to create the perfect mix.



A versatile, sustainable solution

The unique properties of Novec fluids provide a balanced, cost-effective solution for your toughest formulation and performance challenges:

- Low global warming potential (GWP)
- Zero ozone depletion potential
- Not scheduled for regulatory restriction or phase-out
- Neat Novec fluids are non-chlorinated and exempt from the U.S. EPA definitions for Volatile Organic Compounds (VOCs)
- Non-flammable
- Non-conductive
- Excellent materials compatibility
- Non-corrosive
- Low toxicity
- High margin of worker safety
- Sustainable alternative to hydrochlorofluorocarbons (HCFCs), hydrofluorocarbons (HFCs) and other common industrial solvents

Solutions powered by science

3M™ Novec™ Engineered Fluids are based on a proprietary 3M chemistry. The invention of this unique, low-global warming potential chemistry is part of 3M's longstanding commitment to continually improve the environmental, health and safety profiles of our chemical products. The physical properties of these materials also make them an ideal solution for delivering value in many of today's most demanding solvent and lubricant applications:

- **Coatings**
 - Touch screens
 - Protection of electronic components
- **Precision cleaners**
- **Lubricants**
 - Fluorinated lubricants, including dry lubricants
 - Silicones
 - Hydrocarbon lubricants



Meeting your formulating challenges

With Novec fluids, neat and blends, there's no need to settle for only a few of the properties you want—you can have it all.

Engineered for:	To give you:
 Solubility	Freedom to formulate with a wide range of materials including hydrocarbons and fluorocarbons
 Stability	Consistent performance and reduced chance of formulation property changes due to storage or transport
 Compatibility	Compatible with metals, ceramics and most plastics and elastomers
 Low surface tension and viscosity	Improved wetting and sprayability for more uniform application and coverage
 Wide selection of boiling points	Better control over dry times and dripping
 Inerting	May help inert flammable fluids to help improve safety for workers and customers
 Versatility	Improved balance of performance, materials compatibility, safety and environmental properties to help increase value for customers